



FB2026

Specs

Model	FB2026
Hardware	
Image Sensor	1 / 2.7" Mega-Pixel CMOS Sensor
Sensitivity	Color : 0.38Lux@F1.4 /W: 0 Lux@F1.4 (IR LED on)
Lens Type	Vari-focal Lens 3~10.5 mm @ F1.4
View Angle	33.1°(W)~90.7°(T) Horizontal 18.7°(W)~49.1°(T) Vertical
Power over Ethernet	Yes
Audio	G.711(64K) and G.726(32K,24K) audio compression Input : 3.5mm phone jack Output: 3.5mm phone jack, Support 2-way.
Video Output	Yes
I/O	1 DI / 1 DO
	DC 12V Max: 2.76W(IR Off); 4.80W(IR On)

Power Consumption	PoE Max: 3.84W(IR Off); 6.72W(IR On)
Operating Temperature	-10°C ~50°C
Dimensions	83mm (□) x 117mm (H)
Weight	1000g
Network	
Ethernet	10/ 100 Base-T
Network Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, RTSP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour
System	
Video Resolution	1920x1080@30fps, 1280x960@30fps, 1280x720@30fps, 800*600@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps
Video Adjust	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Shutter Time, Sense-Up, D-WDR, Anti Fog, Lens Distortion Correction, Flip, Mirror, Day&Night Adjustable, Red Gain and Blue Gain, Denoise
Triple Streaming	Yes
Image Snapshot	Yes
Full Screen Monitoring	Yes
Privacy Mask	Yes, 5 different areas
Compression Format	H.264/ M-JPEG
Video Bitrates Adjust	CBR, VBR

Motion Detection	Yes, 3 different areas
Triggered Action	Mail, FTP, Save to SD card, Samba
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, QoS/DSCP
IVA features	Tampering Detection
Firmware Upgrade	HTTP mode, can be upgraded remotely
Simultaneous Connection	Up to 10
Micro SD Card Management	
Recording Trigger	Motion Detection, IP check, Network break down(wire only), Schedule, DI
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes

*For detailed warranty information, please visit the warranty & repair (<http://surveillance.aver.com/warranty>) page

**Specifications may vary depending on countries and are subject to change without notice