



E1008

Specs

model		E1008
system		
operating system		embedded Linux
total channel number		8
max. IP camera input		8
max. analog camera input		8
performance		
display (analog)		240 / 200fps (NTSC/PAL)
display (IP)		2M @ 80fps
recording (analog)	compression	H/W H.264
	resolution	NTSC: 352 x 240 (CIF), 720 x 240 (Half-D1), 720 x 480 (D1) PAL: 352 x 288 (CIF), 720 x 288 (Half-D1), 720 x 576 (D1)
	frame rate (NTSC/PAL)	CIF: 240 / 200fps Half-D1: 240 / 200fps D1: 240 / 200fps
recording (IP)	resolution	up to 5 megapixels for one channel, and a total of 16 megapixels for all channels in H.264 / MPEG-4 / MJPEG format
throughput		60 Mbps
storage	internal HDD capacity	1 SATA HDD
	internal RAID support	-
	external HDD support	e-SATA HDD x 1

backup	internal DVD-RW	- (supports external DVD-RW)
interface		
monitor	VGA output	1 (up to 1920 x 1080)
	HDMI output	1 (up to 1920 x 1080)
	TV output	1 (supports hybrid multi-quad output)
	spot output	-
audio	input	8 line-in, 8KHz sampling rate
	output	1 line-out
MIC	input	1 line-in
alarm	sensor (alarm) inputs	4 input voltage: max. DC 6V
	relay output	2 (NO/NC) voltage range: AC 125V / DC 30V switching current: max. 1A
network	Ethernet (RJ45)	2 (10/100/1000 Base-T)
ports	e-SATA	1
	RS-232	-
	RS-485	1 set (Tx+, Tx-, Rx+, Rx-)
	USB 2.0	3 (2 ports on front panel, 1 port on rear panel)
general		
electrical	power input	48W power adapter, DC 12V
environmental	operating temperature	0°C to 40°C
	operating humidity	90% RH
mechanical	dimensions (W x H x D)	245 x 50 x 160 mm
	weight (net)	0.8kg