

FB4026

4 Megapixel, H.265, Bullet IP Camera

VF lens 2.8-12 mm, IR 30 Meters,

View angle 34° ~ 92°



Main Features:

1. 4 Megapixel IR Bullet Real Time IP Camera
2. H.265 / H.264/ M-JPEG Compression
3. External Vari-focal Lens Adjustment
4. Digital Noise Reduction
5. Power over Ethernet
6. Digital Wide Dynamic Range
7. Day & Night Manual Switch Time Control
8. IR LED Built-in 30M
9. IR Cut Filter Mechanism
10. Micro SD Card Backup (Optional)
11. 2-way Audio
12. IP66
13. Cable Management
14. Support iPhone/Android/Apple MAC
15. Free Bundle 32CH Recording Software (NXU Lite)

Hardware	
CPU	Multimedia SoC
RAM	512MB
Flash	256MB
Image Sensor	1 / 3" Megapixel CMOS Sensor
Sensitivity	Color: 0.08 Lux (AGC ON) B/W: 0.03 Lux (AGC ON)
Lens Type	Vari-focal Lens 2.8-12 mm @ F1.4
View Angle	34°~92°(H), 19°~48°(V)
ICR	IR cut Filter Mechanism
I/O	1 DI / 1 DO
Power over Ethernet	Yes
Video Output	Yes
Audio	G.711(64K) and G.726(32K,24K) audio compression Input : 3.5mm phone jack Output: 3.5mm phone jack, Support 2-way.
Power Consumption	DC 12V Max: 6W(IR ON); 3.12W(IR OFF) PoE Max: 7.68W(IR ON); 3.84W(IR OFF)
Operating Temperature	-20°C ~ 60°C [*IR OFF]

Product Specifications



*IR ON: 50°C	
Dimensions	77.4 mm (Ø) x 172 mm (H)
Weight	920g
IR LEDs	
LEDs	28 Units 5φ + 2 Units High Power, 850nm
IR Distance	30M
Network	
Ethernet	10/ 100 Base-T
Network Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour
System	
Video Resolution[16:9]	2592x1520@25fps, 1920x1080@25fps, 1280x720@25fps, 640x360@25fps
Video Adjust	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Night Mode, WDR, Flip, Mirror, Noise Reduction, Day&Night Adjustable
Triple Streaming	Yes
Image Snapshot	Yes
Full Screen Monitoring	Yes
Privacy Mask	Yes, 3 different areas
Compression Format	H.265 / H.264/ M-JPEG
Video Bitrates Adjust	CBR, VBR
Motion Detection	Yes, 3 different areas
Triggered Action	Mail, FTP, Save to SD card, DO, SAMBA
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely
Simultaneous Connection	Up to 10
Micro SD Card Management (Optional)	
Recording Trigger	Motion Detection, IP check, Network break down (wire only),Schedule, DI
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes
Web Browsing Requirement	
OS	Windows 7 or above , Microsoft IE 9.0 or above
Mobile Support	iOS 7 or above, Android 4.0 or above
Hardware Suggested	Intel Dual Core 2.53G,RAM: 1024MB, Graphic card: 128MB

***SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.**



