

# 2MP 4 in 1 ANALOGUE MINI DOME CAMERA

## YAH-322A / YAH-322CQ



### Feature

- 4 in 1 Video output: CVI /TVI/AHD/CVBS 960H
- Resolution up to 1920 x 1080P
- Minimum illumination : 0.01Lux(AGC ON), 0Lux IR on
- 4-area Motion Detection & 4-area Privacy Mask
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR
- OSD menu control
- Designed & Produced in Taiwan with Strict Quality Control



### Specification

| Camera   | MODEL              | YAH-322A                                    | YAH-322CQ              |
|----------|--------------------|---------------------------------------------|------------------------|
|          | CMOS Sensor        | 1/3" 2MP Sony CMOS                          | 1/2.7" 2MP Pixart CMOS |
|          | Effective Picture  | 1920(H) x 1080(V)                           |                        |
|          | Resolution         | 1080P@25/30fps                              |                        |
|          | Min Illumination   | 0.01 Lux(AGC ON) 0 Lux IR on                |                        |
|          | S/N Ratio          | More than 50dB (AGC Off)                    |                        |
|          | OSD                | Support                                     |                        |
|          | UTC                | Support                                     |                        |
|          | Video Output       | CVI/TVI/AHD(1080P)/CVBS 960H adjustable     |                        |
|          | IR LED             | 6PCS Array LED                              |                        |
|          | IR Distance        | 15M                                         |                        |
|          | LENS               | 3.6/6/8mm lens (optional)                   |                        |
| Function | Electronic Shutter | Auto 1/50(60)-1/100000sec                   |                        |
|          | AGC                | 15 level                                    |                        |
|          | Sense Up           | Yes                                         |                        |
|          | D-WDR              | On/Off                                      |                        |
|          | BLC                | BLC/OFF/HSBLC                               |                        |
|          | White Balance      | ATW / AWB / Manual / Outdoor / Indoor / AWC |                        |
|          | Day & Night        | Auto / Color / BW / EXT (OSD switch)        |                        |
|          | DNR                | 2D/3D DNR, multi-levels adjustable          |                        |
|          | Motion             | On / Off (4x zone)                          |                        |
|          | Privacy Mask       | On / Off (4x zone)                          |                        |
| General  | Outdoor            | ---                                         |                        |
|          | Power Consumption  | DC12V ± 10%                                 |                        |
|          | Dimen./Weight      | 93(Φ) x 80(H) mm / 240g                     |                        |
|          | Operation Temp.    | -10℃ ~ 50℃                                  |                        |

Certificate : CE , FCC , RoHS